



## VALVES - MODEL 975

### ELECTRIC DIAPHRAGM BRASS GLOBE VALVE

Available in:

3/4", 1", 1 1/4", 1 1/2", 2", 2 1/2" & 3"

#### FEATURES

- Pressure rating: 200 psi.
- Solid brass construction.
- Water-proof solenoid coil, guaranteed for life of the valve.
- Coil can be rotated 360° and easily removed without removing solenoid operator.
- Slow closing. No water hammer, surge or noise.
- Manual operation in the event of power failure with a solid brass heavy duty drain cock.
- Manual flow control standard on all sizes.
- 110 volts standard with conduit solenoid housing.
- Self-cleaning orifice.
- Minimum differential pressure required 10 PSI

Diaphragm of one-piece molded construction with integral O-ring seal reinforced with 600 lb. test fabric. Three year warranty against defective parts and workmanship.



DIMENSIONS					
SIZE	3/4"	1"	1 1/4"	1 1/2"	2"
Height:	5"	4 1/2"	5 1/2"	8"	9"
Length:	3 1/4"	4 3/8"	5"	6"	7"

VALVE FLOW RATE (GPM)				
PRESSURE DIFFERENTIAL IN PSI				
SIZE	15#	20#	30#"	40#"
3/4"	26	28	39	40
1"	52	60	78	85
1 1/4"	75	95	120	137
1 1/2"	110	125	164	169
2"	160	200	231	250